

ALMAR LT 5

Lighting Towers



Prime Power

Refers to the main power supply, working under 70% average load for unlimited time. 10% overloading is allowed.

Stand-by Power

Refers to the back up power supplied to the varying load for a limited time. Overloading is not allowed.

Generator

		Prime	Stand-by
Power (kVA)	kVA	4,5	5
Power kW	kW		

Generator Model::	ALMAR LT 5
Engine Manufacturer Model:	Alimar / ALMDS5000
Fuel Type:	Dizel
Frequency:	50 Hz
Power Factor:	0,8
Voltage:	220
Fuel Tank Capacity:	lt
Dimensions - L x W x H:	
Weight:	

H: External

K: Container

TBA: To be added

ALMAR LT 5

Lighting Towers



Control Panel



ALM929



AMF9

Comap InteliNano NT Plus

Largest graphic display in its class
AMF and MRS function
User friendly interface
Manual start function
Engine control function

Measurements

Mains and gen. LL - LN voltages
Mains and generator frequency
Mains and generator phase current
Engine protection functions

Connections

3 phase 4 wire, star & delta
3 phase 3 wires, 2 current transformers
2 phase 3 wire
1 phase 2 wire

Communication

PC connection via USB
J1939-CANBUS

Protection Functions

- Overvoltage
- Low voltage
- Voltage asymmetry and phase sequence
- High frequency
- Low frequency
- Short-circuit current
- Overcurrent
- Power factor
- Coolant temperature
- Low oil pressure

Auto Panel Features

- Automatic generator, grid control and fault monitoring
- Easy control with a user-friendly interface from the panel screen
- Remote operation with optional communication cards
- Manual programming with password-protected service interface
- Manual control of generator and transfer panel with buttons on the front panel
- Front panel protection class IP65
- With an operating temperature of -20 C to +70 C and a storage temperature of -40 C to +80 C

ALMAR LT 5



Lighting Towers

Standard Features



Engine

Low fuel consumption and high performance latest technology diesel engines are used with electronic or mechanical governor, water-cooled radiator system, replaceable oil, fuel, air filters.

Alternator

With its robust and compact structure, steel body, maintenance-free single bearing system, brushless, self-excited system and electronic type AVR, alternators suitable for the special needs of different applications are used.

Gen-Set Canopy

Modular cabinets are used in accordance with 2000/14/EC directives, covered with sound and heat insulation flame-resistant sponge, corrosion and rust resistant paint, locks and hinges, large lockable doors on both sides for easy service and maintenance. Exhaust and silencer insulated according to engine suitability. Small and medium power fuel tank is designed as underchassis. Lifting ears on chassis. Vibration prevention wedges are used under the chassis.

Standard Accessories

- Industrial silencer and stainless compensator
- Maintenance-free lead-acid starter battery, cable and stand
- Control module
- Relays and fuses
- Emergency stop button
- 4x300 W led or 4x1000 W projector
- Mechanical mast that can rise up to 7 meters
- Carrier single axle trailer
- Light system suitable for highways
- 4 balance legs
- Forward-reverse drawbar
- 360 degree rotating projector

Optional Features

- Handbrake
- Hydraulic mast
- Double axle trailer
- LED and projector lighting units and types
- Projector position control electrically and mechanically

Other Accessories

- Electric/Manual oil drain pump
- Critical type silencer
- Trailer